

Safety Data Sheet

75% Helium 23.3% nitrogen 1.7% Carbon Dioxide

Section 1: Product and Company Identification

Purity Cylinder Gases,Inc.

2580 28th St SW Wyoming, MI 49519 P: (616)532-2375 www.puritygas.com

Product Code: 75% Helium 23.3% nitrogen 1.7% Carbon Dioxide

Synonyms: Laser Mix 4

Recommended Use: Usage Restrictions:

Section 2: Hazards Identification



Hazard Classification:

Gases Under Pressure

Hazard Statements:

Contains gas under pressure; may explode if heated

Precautionary Statements

Storage:

Protect from sunlight. Store in well-ventilated place.

Section 3: Composition/Information on Ingredients

	CAS#	Concentration
Helium	7440-59-7	75
Nitrogen	7727-37-9	23.3
Carbon Dioxide	124-38-9	1.7

Purity Cylinder Gases,Inc. Generated by the SDS Manager from AsteRisk, LLC. All Rights Reserved page 1 of 7

Date of Preparation: 03/03/2025 10:59:42

	Chemical Substance	Chemical Family	Trade Names
Helium	HELIUM	Inorganic gases	HELIUM GAS; HELIUM COMPRESSED; HELIUM-4; ATOMIC HELIUM; UN 1046; He
Nitrogen	NITROGEN,	Inorganic	DIATOMIC NITROGEN; DINITROGEN; NITROGEN; NITROGEN-14;
	COMPRESSED GAS	gases	NITROGEN GAS; UN 1066; N2
Carbon	CARBON DIOXIDE, GAS	Inorganic	CARBONIC ACID GAS; CARBONIC ANHYDRIDE; CARBON DIOXIDE;
Dioxide		gases	CARBON OXIDE; UN 1013; CO2

Section 4: First Aid Measures

	Skin Contact	Eye Contact	Ingestion	Inhalation	Note to Physicians
Helium	Wash exposed skin with soap and water.	Flush eyes with plenty of water.	If a large amount is swallowed, get medical attention.	If adverse effects occur, remove to uncontaminated area. Give artificial respiration if not breathing. If breathing is difficult, oxygen should be administered by qualified personnel. Get immediate medical attention.	For inhalation, consider oxygen.
Nitrogen	Wash exposed skin with soap and water.	Flush eyes with plenty of water.	If a large amount is swallowed, get medical attention.	If adverse effects occur, remove to uncontaminated area. Give artificial respiration if not breathing. If breathing is difficult, oxygen should be administered by qualified personnel. Get immediate medical attention.	For inhalation, consider oxygen.
Carbon Dioxide	If frostbite or freezing occur, immediately flush with plenty of lukewarm water (105-115 F; 41-46 C). DO NOT USE HOT WATER. If warm water is not available, gently wrap affected parts in blankets. Get immediate medical attention.	Contact with liquid: Immediately flush eyes with plenty of water for at least 15 minutes. Then get immediate medical attention.	Do not induce vomiting.	If adverse effects occur, remove to uncontaminated area. Give artificial respiration if not breathing. If breathing is difficult, oxygen should be administered by qualified personnel. Get immediate medical attention.	For inhalation, consider oxygen.

Section 5: Fire Fighting Measures

	Suitable Extinguishing Media	Products of Combustion	Protection of Firefighters
Helium	Non-flammable. Use suitable extinguishing media for surrounding fire.	Non-flammable	Non-flammableNon-flammable
Nitrogen	Non-flammable. Use suitable extinguishing media for surrounding fire. Cylinders may rupture or explode if exposed to heat.	Non-flammable	 Respiratory protection may be needed for frequent or heavy exposure.
Carbon Dioxide	Non-flammable	Non-flammable	 Any appropriate escape-type, self- contained breathing apparatus. Non-flammable

Section 6: Accidental Release Measures

	Personal Precautions	Environmental Precautions	Methods for Containment
Helium	Keep unnecessary people away, isolate hazard area and deny entry. Stay upwind and keep out of low areas.	Avoid soil, waterways, drains and sewers	Stop leak if possible without personal risk.

Purity Cylinder Gases,Inc. page 2 of 7 Date of Preparation: 03/03/2025 10:59:42

	Personal Precautions	Environmental Precautions	Methods for Containment
Nitrogen	Keep unnecessary people away, isolate hazard area and deny entry. Stay upwind and keep out of low areas.	No significant effects from contamination expected.	Stop leak if possible without personal risk.
Carbon Dioxide	Keep unnecessary people away, isolate hazard area and deny entry. Ventilate closed spaces before entering. Do not touch spilled material.	Subject to California Safe Drinking Water and Toxic Enforcement Act of 1986 (Proposition 65). Keep out of water supplies and sewers.	Stop leak if possible without personal risk.

	Methods for Cleanup	Other Information
Helium	Stop leak, evacuate area. Contact emergency personnel.	None
Nitrogen	N/A	N/A
Carbon Dioxide	Stop leak, evacuate, remove source of ignition.	None

Section 7: Handling and Storage

	Handling	Storage
Helium	Store and handle in accordance with all current regulations and standards. Subject to storage regulations: U.S. OSHA 29 CFR 1910.101.	Keep separated from incompatible substances.
Nitrogen	Store and handle in accordance with all current regulations and standards. Subject to storage regulations: U.S. OSHA 29 CFR 1910.101.	Keep separated from incompatible substances.
Carbon Dioxide	Subject to storage regulations: U.S. OSHA 29 CFR 1910.101. Keep separated from incompatible substances.	Store and handle in accordance with all current regulations and standards

Section 8: Exposure Controls/Personal Protection

	Exposure Guidelines
Helium	HELIUM: ACGIH (simple asphyxiant)
Nitrogen	NITROGEN, COMPRESSED GAS: NITROGEN: ACGIH (simple asphyxiant)
Carbon	CARBON DIOXIDE, GAS: CARBON DIOXIDE: 5000 ppm (9000 mg/m3) OSHA TWA 10000 ppm (18000 mg/m3) OSHA TWA
Dioxide	(vacated by 58 FR 35338, June 30, 1993) 30000 ppm (54000 mg/m3) OSHA STEL (vacated by 58 FR 35338, June 30, 1993) 5000
	ppm ACGIH TWA 30000 ppm ACGIH STEL 5000 ppm (9000 mg/m3) NIOSH recommended TWA 10 hour(s) 30000 ppm (54000
	mg/m3) NIOSH recommended STEL

Engineering Controls

Handle only in fully enclosed systems.

	Eye Protection	Skin Protection	Respiratory Protection
Helium	Eye protection not required, but recommended.	Protective clothing is not required.	Non-flammable
Nitrogen	Eye protection not required, but recommended.	Protective clothing is not required.	Respiratory protection may be needed for frequent or heavy exposure.
Carbon Dioxide	For the gas: Eye protection not required, but recommended. For the liquid: Wear splash resistant safety goggles. Contact lenses should not be worn. Provide an emergency eye wash fountain and quick drench shower in the immediate work area.	For the gas: Protective clothing is not required. For the liquid: Wear appropriate protective, cold insulating clothing.	Any appropriate escape- type, self-contained breathing apparatus.

General Hygiene considerations

- Avoid breathing vapor or mist
- Avoid contact with eyes and skin
- Wash thoroughly after handling and before eating or drinking

Section 9: Physical and Chemical Properties

	Physical State	Appearance	Color	Change in Appearance	Physical Form	Odor	Taste
Helium	Gas	Colorless	Colorless	N/A	Gas	Odorless	Tasteless
Nitrogen	Gas	Clear	Colorless	N/A	Gas	Odorless	Tasteless
Carbon Dioxide	Gas	Colorless	Colorless	N/A	Gas	Odorless	Acid taste

Purity Cylinder Gases,Inc. page 3 of 7 Date of Preparation: 03/03/2025 10:59:42

	Flash Point	Flammability	Partition Coefficient	Autoignition Temperature	Upper Explosive Limits	Lower Explosive Limits
Helium	Not flammable	Not available	Not available	Nonflammable	Nonflammable	Nonflammable
Nitrogen	Not flammable	Not available	Not available	Nonflammable	Nonflammable	Nonflammable
Carbon Dioxide	Not flammable	Not available	N/A	Nonflammable	Nonflammable	Nonflammable

	Boiling Point	Freezing Point	Vapor Pressure	Vapor Density	Specific Gravity	Water Solubility	рH	Odor Threshold	Evaporation Rate	Viscosity
Helium	-452 F (- 269 C)	-458 F (- 272 C) at 26 atm	1719 mmHg at -268 C	0.138 (Air=1)	Not applicable	0.94% at 0 C	Not applicable	Not available	Not applicable	0.02012 cP at 26.8 C
Nitrogen	-321 F (- 196 C)	-346 F (- 210 C)	760 mmHg @ -196 C	0.967 (Air=1)	Not applicable	1.6% @ 20 C	Not applicable	Not available	Not applicable	0.01787 cP @ 27 C
Carbon Dioxide	Not available	-71 F (-57 C) @ 4000 mmHg	43700 mmHg @ 21 C	1.5 (Air=1)	1.522 @ 21 C	Soluble	3.7 (saturated aqueous solution) @ 101.3 kPa (carbonic acid)	Not available	Not applicable	0.01657 cP @ 0 C

	Molecular Weight	Molecular Formula	Density	Weight per Gallon	Volatility by Volume	Volatility	Solvent Solubility
Helium	4.0026	He	0.1785 g/L at 0 C	Not available	100%	Not applicable	Insoluble: Not available
Nitrogen	28.0134	N2	1.2506 g/L	Not available	100%	1	Soluble: Liquid ammonia
Carbon Dioxide	44.01	C-O2	0.114	Not available	Not applicable	Not applicable	Soluble: Alcohol, acetone, hydrocarbons, organic solvents

Section 10: Stability and Reactivity

	Stability	Conditions to Avoid	Incompatible Materials
Helium	Stable at normal temperatures and pressure.	Stable at normal temperatures and pressure.	No data available.
Nitrogen	Stable at normal temperatures and pressure.	Stable at normal temperatures and pressure.	Metals, oxidizing materials
Carbon Dioxide	Stable at normal temperatures and pressure.	Stable at normal temperatures and pressure.	Combustible materials, oxidizing materials, metal salts, reducing agents, metal carbide, metals, bases

	Hazardous Decomposition Products	Possibility of Hazardous Reactions		
Helium	Miscellaneous decomposition products	Will not polymerize.		
Nitrogen	Oxides of nitrogen	Will not polymerize.		
Carbon Dioxide	Carbon monoxide	Will not polymerize.		

Section 11: Toxicology Information

Acute Effects

	Oral LD50	Dermal LD50	Inhalation
Helium	Not available	Not available	Nausea, vomiting, difficulty breathing, irregular heartbeat, headache, fatigue, dizziness, disorientation, emotional disturbances, tingling sensation, loss of coordination, suffocation, convulsions, unconsciousness, coma
Nitrogen	Not available	Not available	Nausea, vomiting, difficulty breathing, headache, drowsiness, dizziness, tingling sensation, loss of coordination, convulsions, coma
Carbon Dioxide	Not established	Not established	Ringing in the ears, nausea, irregular heartbeat, headache, drowsiness, dizziness, tingling sensation, visual disturbances, suffocation, convulsions, coma

	Eye Irritation	Skin Irritation	Sensitization
Helium	Liquid: frostbite, blurred vision	Liquid: frostbite	Difficulty breathing
Nitrogen	Contact with rapidly expanding gas may cause burns or frostbite	No information on significant adverse effects	Difficulty breathing
Carbon Dioxide	Irritation, frostbite, blurred vision	Liquid: blisters, frostbite	Difficulty breathing

Chronic Effects

	Carcinogenicity	Mutagenicity	Reproductive Effects	Developmental Effects
Helium	Not available	Not available	Not available	No data
Nitrogen	Not hazardous	Not available	Not available	No data
Carbon Dioxide	Not available	Not established	Available.	No data

Section 12: Ecological Information

Fate and Transport

	Eco toxicity	Persistence / Degradability	Bioaccumulation / Accumulation	Mobility in Environment
Helium	Fish toxicity: Not available Invertibrate toxicity: Not available Algal toxicity: Not available Phyto toxicity: Not available Other toxicity: Not available	Not available	Not available	Not available
Nitrogen	Fish toxicity: Not available Invertibrate toxicity: Not available Algal toxicity: Not available Phyto toxicity: Not available Other toxicity: Not available	Not available	Not available	Not available
Carbon Dioxide	Fish toxicity: 150000 ug/L 48 day(s) (Mortality) Brown trout (Salmo trutta) Invertibrate toxicity: Not available Algal toxicity: Not available Phyto toxicity: Not available Other toxicity: Not available	Relatively non-persistent in the environment. Moderately volatile from water.	Accumulates very little in the bodies of living organisms.	Leaches through the soil

Section 13: Disposal Considerations

Helium	Dispose in accordance with all applicable regulations.
Nitrogen	Dispose in accordance with all applicable regulations.
Carbon Dioxide	Dispose in accordance with all applicable regulations.

Section 14: Transportation Information

U.S. DOT 49 CFR 172.101

DOT Information For This Mixture

BOT Information For This wixture					
Shipping Name	Compressed gas, n.o.s. (Helium, Nitrogen)				
UN Number UN1956					
Hazard Class	2.2				
Hazard Information	Non-Flammable Gas				

Purity Cylinder Gases,Inc. page 5 of 7 Date of Preparation: 03/03/2025 10:59:42

Individual Component Information

	Proper Shipping Name	ID Number	Hazard Class or Division	Packing Group	Labeling Requirements	Passenger Aircraft or Railcar Quantity Limitations	Cargo Aircraft Only Quantity Limitations	Additional Shipping Description
Helium	Helium, compressed	UN1046	2.2	Not applicable	2.2	75 kg or L	150 kg	N/A
Nitrogen	Nitrogen, compressed	UN1066	2.2	Not applicable	2.2	75 kg or L	150 kg	N/A
Carbon Dioxide	Carbon dioxide	UN1013	2.2	Not applicable	2.2	75 kg or L	150kg	None

Canadian Transportation of Dangerous Goods

	Shipping Name	UN Number	Class	Packing Group / Risk Group
Helium	Helium, compressed	UN1046	2.2	Not applicable
Nitrogen	Nitrogen, compressed	UN1066	2.2	Not applicable
Carbon Dioxide	Carbon dioxide	UN1013	2.2	Not applicable

Section 15: Regulatory Information

U.S. Regulations

	CERCLA Sections SARA 355.30		SARA 355.40	
Helium	Not regulated.	Not regulated.	Not regulated.	
Nitrogen	Not regulated.	Not regulated.	Not regulated.	
Carbon Dioxide	Not regulated.	Not regulated.	Not regulated.	

SARA 370.21

	Acute	Chronic	Fire	Reactive	Sudden Release
Helium	Yes	No	No	No	Yes
Nitrogen	Yes	No	No	No	Yes
Carbon Dioxide	Yes	No	No	No	Yes

SARA 372.65

Helium	Not regulated.	
Nitrogen	Not regulated.	
Carbon Dioxide	Not regulated.	

OSHA Process Safety

Helium	Not regulated.	
Nitrogen	Not regulated.	
Carbon Dioxide	Not regulated.	

State Regulations

	CA Proposition 65
Helium	Not regulated.
Nitrogen	Not regulated.
Carbon Dioxide	Not regulated.

Canadian Regulations

Odriddidii itog	Jaiations
	WHMIS Classification
Helium	Α
Nitrogen	Α
Carbon Dioxide	Α

National Inventory Status

Hational IIII	itory otatao		
	US Inventory (TSCA)	TSCA 12b Export Notification	Canada Inventory (DSL/NDSL)
Helium	Listed on inventory.	Not listed.	Not determined.
Nitrogen	Listed on inventory.	Not listed.	Listed on inventory.
Carbon Dioxide	Listed on inventory.	Not listed.	Listed on inventory.

Section 16: Other Information

	NFPA Rating
Helium	HEALTH=0 FIRE=0 REACTIVITY=0 SPECIAL=SA
Nitrogen	HEALTH=0 FIRE=0 REACTIVITY=0 SPECIAL=SA
Carbon Dioxide	HEALTH=3 FIRE=0 REACTIVITY=0 SPECIAL=SA

^{0 =} minimal hazard, 1 = slight hazard, 2 = moderate hazard, 3 = severe hazard, 4 = extreme hazard

Purity Cylinder Gases,Inc. Generated by the SDS Manager from AsteRisk, LLC. All Rights Reserved page 7 of 7 Date of Preparation: 03/03/2025 10:59:42