

Safety Data Sheet Liquid Helium

Section 1: Product and Company Identification

Purity Cylinder Gases,Inc. 2580 28th St SW Wyoming, MI 49519 P: (616)532-2375 www.puritygas.com

Product Code: Liquid Helium

Part Number: HE LC

Section 2: Hazards Identification



Hazard Classification: Gases Under Pressure

Hazard Statements:

Contains gas under pressure; may explode if heated

Precautionary Statements

Storage:

Protect from sunlight. Store in well-ventilated place.

Section 3: Composition/Information on Ingredients

CAS # 7440-59-7

Date of Preparation: 03/03/2025 11:47:39

Chemical Substance	Chemical Family	Trade Names
HELIUM	Inorganic gases	HELIUM REFRIGERATED LIQUID; LIQUID HELIUM; HELIUM-4; ATOMIC HELIUM; UN 1046; He; UN 1963

Section 4: First Aid Measures

Skin Contact	Eye Contact	Ingestion	Inhalation	Note to Physicians
In case of frostbite, wash exposed skin with warm water not to exceed 105F (41C). Seek medical attention immediately.	Flush eyes with plenty of water.	If a large amount is swallowed, get medical attention.	If adverse effects occur, remove to uncontaminated area. Give artificial respiration if not breathing. If breathing is difficult, oxygen should be administered by qualified personnel. Get immediate medical attention.	For inhalation, consider oxygen.

Section 5: Fire Fighting Measures

Suitable Extinguishing Media	Products of Combustion	Protect	ion of Firefighters
Non-flammable. Use suitable extinguishing media for surrounding fire.	Non-flammable	•	Non-flammable
		•	Non-flammable

Section 6: Accidental Release Measures

Personal Precautions	Environmental Precautions	Methods for Containment
Keep unnecessary people away, isolate hazard area and deny entry. Stay upwind and keep out of low areas. Liquid helium can freeze air, oxygen, and other gases.	Avoid soil, waterways, drains and sewers	Stop leak if possible without personal risk. Allow spilled liquid to evaporate.

Methods for Cleanup	Other Information
Stop leak, evacuate area. Contact emergency personnel. Test for sufficient oxygen, especially in confined areas, before allowing reentry.	None

Section 7: Handling and Storage

Handling	Storage
Store and use with adequate ventilation. Firmly secure cylinders upright to keep them from falling or being knocked over. Screw valve protection cap	Do not get liquid in eyes, on skin, or clothing. Protect cylinders from damage. Use a suitable hand truck to move cylinders; do not
firmly in place by hand. Store only where temperature will not exceed 125F (52C). Store full and empty cylinders separately. Use a first-in, first-out	drag, roll, slide, or drop. Open valve slowly. Close cylinder valve after each use; keep closed even when empty. If valve is hard to
inventory system to prevent storing full cylinders for long periods.	open, discontinue use and contact your supplier

Section 8: Exposure Controls/Personal Protection

Exposure Guidelines
HELIUM: ACGIH (simple asphyxiant)

Engineering Controls

Handle only in fully enclosed systems.

That have drive and the state of the state o			
Eye Protection	Skin Protection	Respiratory Protection	
Eye protection not required, but recommended.	Cryogenic, protective clothing when required.	Non-flammable	

Purity Cylinder Gases,Inc. page 2 of 4 Generated by the SDS Manager from AsteRisk, LLC. All Rights Reserved Date of Preparation: 03/03/2025 11:47:39

General Hygiene considerations

- Avoid breathing vapor or mist
- Avoid contact with eyes and skin
- Wash thoroughly after handling and before eating or drinking

Section 9: Physical and Chemical Properties

Physical State	Appearance	Color	Change in Appearance	Physical Form	Odor	Taste
Cryogenic Liquid	Colorless	Colorless	N/A	Gas	Odorless	Tasteless

Flash Point	Flammability	Partition Coefficient	Autoignition Temperature	Upper Explosive Limits	Lower Explosive Limits
Not flammable	Not available	Not available	Nonflammable	Nonflammable	Nonflammable

Boiling Point	Freezing Point	Vapor Pressure	Vapor Density	Specific Gravity	Water Solubility	рH	Odor Threshold	Evaporation Rate	Viscosity
-452 F	-458 F (-	1719	0.138	Not	0.94% @	Not	Not	High	0.02012
(-269 C)	272 C) @ 26 atm	mmHg @ -268 C	(Air=1)	applicable	0 C	applicable	available		cP @ 26.8 C

Molecular Weight	Molecular Formula	Density	Weight per Gallon	Volatility by Volume	Volatility	Solvent Solubility
4.0026	He	0.1785 g/L @ 0 C	Not available	100%	Not applicable	Insoluble: Not available

Section 10: Stability and Reactivity

Stability	Conditions to Avoid	Incompatible Materials
Stable at normal temperatures and pressure.	Stable at normal temperatures and pressure.	Avoid carbon steel.

Hazardous Decomposition Products	Possibility of Hazardous Reactions
Miscellaneous decomposition products	Will not polymerize.

Section 11: Toxicology Information

Acute Effects

Oral LD50	Dermal LD50	Inhalation
Not available	Not available	Nausea, vomiting, difficulty breathing, irregular heartbeat, headache, fatigue, dizziness, disorientation, emotional disturbances, tingling sensation, loss of coordination, suffocation, convulsions, unconsciousness, coma

Eye Irritation	Skin Irritation	Sensitization
Liquid: frostbite, blurred vision	Liquid: frostbite	Difficulty breathing, can cause rapid suffocation

Chronic Effects

Carcinogenicity	Mutagenicity	Reproductive Effects	Developmental Effects
Not available	Not available	Not available	No data

Section 12: Ecological Information

Fate and Transport

Eco toxicity	Persistence / Degradability	Bioaccumulation / Accumulation	Mobility in Environment
Fish toxicity: Not available Invertibrate toxicity: Not available Algal toxicity: Not available Phyto toxicity: Not available Other toxicity: Not available	Not available	Not available	Not available

Purity Cylinder Gases,Inc. page 3 of 4 Generated by the SDS Manager from AsteRisk, LLC. All Rights Reserved Date of Preparation: 03/03/2025 11:47:39

Section 13: Disposal Considerations

Dispose in accordance with all applicable regulations. Return empty container to supplier.

Section 14: Transportation Information

U.S. DOT 49 CFR 172.101

Proper Shipping Name	ID Number	Hazard Class or Division	Packing Group	Labeling Requirements	Passenger Aircraft or Railcar Quantity Limitations	Cargo Aircraft Only Quantity Limitations	Additional Shipping Description
Helium, REFRIGERATED LIQUID	UN1963	2.2	Not applicable	2.2	75 kg or L	150 kg	N/A

Canadian Transportation of Dangerous Goods

Shipping Name	UN Number	Class	Packing Group / Risk Group	
Helium, LIQUID	UN1963	2.2	Not applicable	

Section 15: Regulatory Information

U.S. Regulations

CERCLA Sections	SARA 355.30	SARA 355.40
Not regulated.	Not regulated.	Not regulated.

SARA 370.21

Acute	Chronic	Fire	Reactive	Sudden Release
Yes	No	No	No	Yes

SARA 372.65

Not regulated.

OSHA Process Safety

Not regulated.

State Regulations

CA Proposition 65 Not regulated.

Canadian Regulations

WHMIS Classification

National Inventory Status

US Inventory (TSCA)	TSCA 12b Export Notification	Canada Inventory (DSL/NDSL)	
Listed on inventory.	Not listed.	Not determined.	

Section 16: Other Information

NFPA Rating

HEALTH=3 FIRE=0 REACTIVITY=0 SPECIAL=SA

0 = minimal hazard, 1 = slight hazard, 2 = moderate hazard, 3 = severe hazard, 4 = extreme hazard